

HINGED REFRIGERATION DOORS

- Easy installation and use
- Elegant design and excellent compatibility
- Specially designed rubber seal with integrated heaters
- Specially designed for durability and longevity

TECHNICAL SPECIFICATIONS	
Operating temperature range (+/-)	from -24°C to +60°C
Panel thicknesses for positive working area (+)	ISO 60 mm
Panel thicknesses for negative working area (-)	ISO 100 mm

STANDARD DOOR DIMENSIONS		
Door type	BUILT IN DOOR	
	SINGLE LEAF	DOUBLE LEAF
Maximal door dimension clear opening	width 1500 mm x height 2500 mm	width 2400 mm x height 3000 mm
REFRIGERATION DOOR custom made	Possibility of producing non standard door dimensions, in a step of increment of 100mm	



BUILT IN DOOR



DOUBLE LEAF DOOR



HINGES

- The doors are equipped with hinges made from a quality composite
- Every hinge can be adjusted on all three axes, facilitating a precise centring of the door

LOCK

- The doors are equipped with locks made from a high-quality composite, with a lock cylinder in accordance with DIN EN 179
- ION finishing

SAFETY

- The doors are equipped with a fluorescently labelled "ANTIPANIC" mechanism to open the door from the inside (BS EN179:2008)

SPECIAL TEMPERATURE PROTECTION

- Specially designed rubber seal with integrated heaters

OPTIONS:

- Guideway passage
- 4 types of floor threshold
- PVC profiles
- Hinged double leaf door

APPLICATION:

- Cold rooms
- Storage facilities